

PLAH Series

Remote Mounted, L-Band Line Amplifiers with slope compensation.



The **PLAH series** remote mounted L-Band line amplifier units from Peak Communications are designed to overcome the losses associated with cross-site installations, whilst incorporating user variable gain & slope controls for optimisation of the RF chain performance & providing ultimate flexibility during commissioning.

The units are DC powered and will accept a wide range of DC voltages, either multiplexed onto the IFL or via a separate connection & can be offered with the **OPS18a/OPS18b** outdoor AC/DC PSU's.

Constructed of high-grade components to give the ultimate gain flatness and stability performance, they are offered in a fully weatherproof sealed chassis designed for mounting in outdoor, exposed locations.








Provided with Ethernet based remote control as standard, they are available with the low-cost **PLAH-LC** plug-in hand-held local controller module for ease of adjustment at the antenna/ hub during commissioning/ maintenance.

High Grade Line Amplifier Products;

PLAH-Tx	950-2150MHz, single channel (output compression optimised for transmit systems)
PLAH-DTx	950-2150MHz, dual channel (output compression optimised for transmit systems)
PLAH-Rx	950-2150MHz, single channel (noise figure optimised for receive systems)
PLAH-DRx	950-2150MHz, dual channel (noise figure optimised for receive systems)
PLAH-Tx-Rx	950-2150MHz, dual channel, one transmit & one receive channel.

For other 'non-standard' frequency requirements, please contact the factory.
 For multi-channel units in larger chassis, please consult the factory.
 For equivalent rack mountable units, please see ILA, ILAH & DLA series datasheet.

Peak Features

-  User variable gain & slope compensation, as standard
-  High gain flatness and stability performance
-  Amplifier low current alarm monitoring
-  Comprehensive Ethernet control as standard plus optional hand-held local control module
-  Rugged weatherproof housing
-  Multi-channel units available in larger chassis
-  Temperature compensated for thermal stability and fast warm-up



PLAH series - Typical Specification

Input

Frequency	950-2150MHz
Connector	50Ω, N-Type (f)
Return loss;	
Tx;	18dB typ., 14dB min.
Rx;	16dB typ., 14dB min.

Output

Connector	50Ω, N-Type (f)
Return loss;	
Tx;	14dB typ., 12dB min.
Rx;	18dB typ., 16dB min.

RF Performance

Gain	20dB min.
Option 4a;	30dB nom.
Option 4b;	40dB nom.
<i>Note: for other gain requirements please contact the factory</i>	
Gain flatness	±0.5dB at slope setting 0dB
Active directivity	22dB typ., 20dB min.
RF input power	+10dBm max (no load, no damage)

Tx configuration (optimised for output compression)

Gain (dB)	Slope (dB)	Noise figure (dB)	1dBGCP (dBm)
20	0	12.5	+17
20	5	13.5	+17
20	10	17.5	+17
10	0	15.5	+16
10	5	19	+11
10	10	23.5	+10
0	0	23.0	+6
0	5	28.0	+1
0	10	33.0	0

Rx configuration (optimised for noise figure)

Gain (dB)	Slope (dB)	Noise figure (dB)	1dBGCP (dBm)
20	0	4	+6
20	5	4	+1
20	10	4.5	0
10	0	4.5	-4
10	5	4.5	-9
10	10	6.0	-10
0	0	6.0	-14
0	5	7.5	-19
0	10	11.5	-20

Linear Active Slope compensation

Provides user settable positive slope compensation for internal circuitry & external primarily cross-site cables.

Note: option 4 gain choice will determine 'surplus' available for external compensation (for details contact factory).

Pivot point	2150MHz
Range	-2 to +10dB nom., user adjustable

Electronically Variable Attenuation

Attenuation range	30dB
Step size	0.5dB

10MHz Reference Pass-through (Option 1, 1a)

Allows 10MHz reference fed into the unit (multiplexed onto L-Band) to 'pass-through'. For alternative configurations please contact the factory.

DC Pass-through for BUC/LNB powering (Option 1a)

Allows DC fed into the unit (multiplexed onto L-Band) to 'pass-through', typically to power an external BUC/ BDC/ LNB.

Mechanical

Width	123mm (4.85")
Height	172mm (6.8"), plus connections & mounting flanges
Depth	55mm (2.16")
<i>Note: size increases with options 1 & 2 to H223x W147x D56mm</i>	
Construction	Die-cast Aluminium, IP66 rated
Weight	1.4kgs (3lbs) approx.

Environmental

Operating temp	-25°C to +55°C (less solar gain)
Option 12;	-40°C to +55°C (less solar gain), with extended warm-up time for cold start operation & higher current
Humidity	0-100% condensing
EMC	EN 55022, part B & EN 50082-1
Safety	EN 60950

Power Supply

Voltage	+16.5 to +35VDC
Current	500mA max
Connection	Fed in on 5-pin circular weatherproof (mating part supplied)
Option 2a;	Fed in on L-Band cable
Option 2b;	Fed in on the 5-pin control connection as well as the L-Band cable

Control System Interface


Remote control	Ethernet; embedded web server & SNMP network management support (RJ45, sealed, mating parts provided)
Local control	PLAH-LC plug-in unit for local control, allowing gain & slope adjustment
Alarms	Summary alarm contacts
Connection	multi-pin circular weatherproof (mating part supplied)

Options

- 1) 10MHz reference pass-through on the L-Band connection.
- 1a) 10MHz reference & DC (2A max.) pass-through on the L-Band connection.
- 2a) DC input connection multiplexed onto the L-Band cable replacing the wired connection to the 5-pin control interface connector.
- 2b) DC input connection multiplexed onto the L-Band cable as well as the 5-pin control interface connector.
- 4a) Increased gain to 30dB nom.
- 4b) Increased gain to 40dB nom.
- 12) Low temperature operation to -40°C
- 16) Factory pre-set IP address

Note: the addition of options can modify the typical specification, for details please consult the factory

Connector panel view (sample)



PEAK
COMMUNICATIONS

Peak Communications reserves the right to alter the specifications of this equipment without prior notice. PLALH2150series-210920.

Peak Communications Ltd., Unit 1, The Woodvale Centre, Woodvale Road, Brighouse, West Yorkshire, HD6 4AB, U.K.

Tel; +44 (0)1484 714200 Sales; +44 (0)1484 714229 Fax; +44 (0)1484 723666 Email; sales@peakcom.co.uk Web; www.peakcom.co.uk